

GoEasy Presence Reference

一、用途

1. 订阅客户端上下线实时状态变化
2. 获取当前在线客户数量和在线客户列表

二、操作步骤

1. 注册 userId (如果不需要在线用户列表, 可以跳过)

```
var goeasy = new GoEasy({  
    appkey: '{appkey}',  
    userId: '{user.uuid}',  
    userData: '{用户附加信息, 字符串类型, 不超过 300K}'  
});
```

2. 订阅用户在线状态

2.1 示例代码

```
goeasy.subscribePresence({  
    channel: 'channel_A',  
    onPresence: function (presenceEvents) {
```

```
//返回值 presenceEvents 示例

{
    "clientAmount": 2, //在线客户端数量
    "userAmount": 1, //在线用户数量
    "events": [
        {
            "clientAmount": 1,
            "userAmount": 1,
            "events": [
                {
                    "action": "join",
                    "userId": "user_id_1", //用户 id
                    "userData": "derek" //用户附加信息
                },
                {
                    "action": "offline",
                    "userId": "user_id_2",
                }
            ]
        }
    ]
}
```

```
        "userData": "Jam"

    }

]

};

]

}

});

});
```

2.2 action 说明:

Join: 客户端订阅 channel 成功
leave: 客户端取消 channel 成功
offline: 客户端下线或断网
online: 之前订阅成功的客户端，在断网后，重连成功

2.3 相关事件监听:

```
goeasy.subscribePresence({

    channel: 'channel_A',
```

```
//订阅 Presence 成功
onSuccess: function () {
    alert('Presence subscription success.');
},
//订阅 Presence 失败
onFailed: function (error) {
    alert('Presence subscription failure.');
},
//当有客户端状态发生变化
onPresence: function (presenceEvents) {
    var data = JSON.stringify(presenceEvents)
    alert('Presence:' + data );
}
});
```

2.4 取消订阅用户在线状态

```
goeasy.unsubscribePresence({
    channel: 'demo_channel',
```

```
//取消成功
onSuccess: function () {
    alert("取消订阅 presence 成功.")
},
//取消失败
onFailed: function (error) {
    alert("取消订阅 presence 失败.")
}
});
```

3. 查询当前在线用户

3.1 Javascript

```
goeasy.hereNow(
{
    channels: ['channel_A', "channel_B"], //要查询的 channel 列表
    includeUsers: true, //可选项，是否返回用户列表，默认 false
    distinct: true //可选项，是否过滤相同的 userId，默认 false
},
function (response) {
    //response 示例
```

```
{  
    "code": 200,  
    "content": {  
        "channels": {  
            "channel_A": {  
                "channel": "channel_A",  
                "clientAmount": 1, //在线客户端数量  
                "userAmount": 1, //在线用户数量  
                "users": [ //在线用户列表  
                    {  
                        "id": "user_id_1", //用户 id  
                        "data": "derek" //用户附加信息  
                    }  
                ]  
            },  
            "channel_B": {  
                "channel": "channel_B",  
            }  
        }  
    }  
}
```

```
        "clientAmount": 0,  
        "userAmount": 0,  
        "users": []  
    }  
}  
}  
}  
}  
);
```

3.2 Rest API

Request:

```
http://<Rest Host>/presence?appkey={appkey}&channel={channel}&includeusers={includeusers}&distinct={distinct}
```

参数:

channel //必须项，一个请求可以包含多个 channel
includeusers //是否返回用户列表，可选项，默认 false
distinct //是否过滤相同的 userId，可选项，默认 false

Response JSON:

```
//response 示例  
{  
    "code": 200,  
    "content": {  
        "channels": {  
            "channel_A": {  
                "channel": "channel_A",  
                "clientAmount": 1, //在线客户端数量  
                "userAmount": 1, //在线用户数量  
                "users": [ //在线用户列表  
                    {  
                        "id": "user_id_1", //用户 id  
                        "data": "derek" //用户附加信息  
                    }  
                ]  
            },  
        }  
    }  
}
```

```
"channel1_B": {  
    "channel": "channel_B",  
    "clientAmount": 0,  
    "userAmount": 0,  
    "users": []  
}  
}  
}
```

3.3 Java

```
升级 Java sdk 至 0.3.10  
goEasy.presence(Arrays.asList("channel_A", "channel_B"),  
    false, // 是否包含用户  
    false, // 是否过滤重复 userId  
    new PresenceListener() {  
        @Override  
        public void onSuccess(Presences presences) {
```

```
//presences 示例

{
    "channels": {
        "channel_A": {
            "channel": "channel_A",
            "clientAmount": 1, //在线客户端数量
            "userAmount": 1, //在线用户数量
            "users": [          //在线用户列表
                {
                    "id": "user_id_1", //用户 id
                    "data": "derek"   //用户附加信息
                }
            ]
        },
        "channel_B": {
            "channel": "channel_B",
            "clientAmount": 0,
        }
    }
}
```

```
        "userAmount": 0,  
        "users": []  
    }  
}  
}  
}  
  
public void onFailed(GoEasyError error) {  
    throw new UnsupportedOperationException("Not yet implemented");  
}  
});
```

三、资费

1. 服务器每推送一条 presenceEvents，扣减消息量 1 条
2. 每个客户端收到一条一条 presenceEvents 扣减消息量 1 条
3. 每查询一次当前在线用户，减扣消息量 1 条